



CY1 1 1 2 GROUSEMOOR CHUNKY TOTE-ALLY DEVOTED BAG

Measurements : Height exc strap: 27cm, Width: 32cm, Depth: 11cm

Materials

Grousemoor Chunky Main (M) – 0060 Thistle 3 x 100g balls

Contrast (C) – 6964 Fuchsia 2x 100g balls

2 – 5½mm needles

Cable needle

Zip length 30cm

Stitch holder

4 curtain rings 28mm diameter 4 safety pins

Tension – 16 sts and 23 rows = 10cm measured over stst using 5½mm needles.

IT IS ESSENTIAL TO WORK TO THE STATED TENSION TO ENSURE THE CORRECT SIZING. If you tension square has less stitches, use a thinner needle, if more, use a thicker needle.

Abbreviations

Mb: make bobble – (k1,yfwd,k1,yfwd,k1) all into next st, turn, p5turn,k5,turn,p2tog,p1,p2tog,turn,sl 1,k2tog,psso

Cr4L: sl next two sts onto cn, hold at back of work,p2,k2 from cn

Cr4R: sl next two sts onto a cn, hold at back of work,k2,p2 from cn

C4B: sl next two sts onto cn, hold at back of work,k2,k2 from cn

C4F: sl next two sts onto cn, hold at front of work,k2,k2 from cn

Cable panel

(worked over 17 sts, and using M throughout except for bobble which uses C)

Row 1(RS) – P4, C4B, K1, C4F, P4.

Row 2 – K4, P2, K1, [P1, K1] twice, P2, K4.

Row 3 – P2, C4B, K1, [P1, K1] twice, C4F, P2.

Row 4 – K2, P2, K1, [P1, K1] 4 times, P2, K2.

Row 5 – P2, K3, [P1, K1] 4 times, K2, P2.

Row 6 – As row 4.

Rows 7 and 8 – As rows 5 and 6.

Row 9 – P2, Cr4L, K1, [P1, K1] twice, Cr4R, P2.

Row 10 – As row 2.

Row 11- P4, Cr4L, K1, Cr4R, P4.

Row 12 – K6, P2, K1, P2, K6.

Row 13 – P6, K2, using C make bobble, then using M, K2, P6.

Row 14 – K6, P5, K6.

These 14 rows form cable panel.

Back and front (alike)

Using 5½mm needles and M, cast on 67 sts.

Next row (RS) – P3, K9, *P6, K2, using C make bobble, then using M, K2, P6, K9, rep from * once more, P3.

Next row – K3, P9, *K6, P5, K6, P9, rep from * once more, K3.

Commence patt

Row 1 (RS) – P3, K9, *wk row 1 of cable panel across next 17 sts, K9, rep from * once more, P3.

Row 2 – K3, P9, *wk row 2 of cable panel, P9, rep from * once more, K3.

Wk 16 rows more in patt as now set, ending with row 4 of cable panel.

Dec row – P3, K2tog, K5, sl1, K1, psso, *wk row 5 of cable panel, K2tog, K5, sl1, K1, psso, rep from * once more, P3. 61 sts.

Next row – K3, P7, *wk row 6 of cable panel, P7, rep from * once more, K3.

Wk 14 rows more in patt as now set, ending with row 6 of cable panel.

Dec row – P3, K2tog, K3, sl1, K1, psso, *wk row 7 of cable panel, K2tog, K3, sl1, K1, psso, rep from * once more, P3. 55 sts.

Next row – K3, P5, *wk row 8 of cable panel, P5, rep from * once more, K3.

Wk 14 rows more in patt as now set, ending with row 8 of cable panel.

Dec row – P3, K2tog, K1, sl1, K1, psso, *wk row 9 of cable panel, K2tog, K1, sl1, K1, psso, rep from * once more, P3. 49 sts.

Next row – K3, P3, *wk row 10 of cable panel, P3, rep from * once more, K3.

Wk 4 rows more in patt as now set, ending with row 14 of cable panel.

Dec row – K1, K2tog, K9, sl1, K1, psso, K1, K2tog, K15, sl1, K1, psso, K1, K2tog, K9, K2tog, K1. 43 sts.

Commence moss st patt

Row 1 (WS) – K1, *P1, K1, rep from * to end.

This row forms moss st patt.

Wk 6 rows more in moss st patt.

Next row – Patt 9, sl last 5 sts just worked onto a safety pin, patt 30, sl last 5 sts just worked onto a safety pin, patt 4.

Next row – Patt 4, cast on 5 sts, patt 25, cast on 5 sts, patt 4. 43 sts.

Wk 8 rows more in patt.

Break off M, join in C.

Beg with a K row, wk 5 rows in stst.

Knit 2 rows.

Cast off knitwise.

Ring flaps (all 4 alike)

Using 5½mm needles and M, and with WS facing, patt across 5 sts on safety pin.

Wk 6 rows more in patt.

Cast off in patt.

Thread flap through ring, and sew cast off edge to cast on sts to enclose the ring.

Sides and base

Using 5½mm needles and M, cast on 7 sts.

Wk 18 rows in moss st patt as given for back and front.

Keeping patt correct and working all inc sts into patt, inc 1 st at each end of the next and every

folll 12th row until 19 sts are on the needle.

Wk 17 rows straight.

(Mark each end of last row to indicate start of base.)

Cont in moss st patt until wk (when slightly stretched) fits across cast on edge of back, ending with a WS row.

(Mark each end of last row to indicate end of base.)

Wk 18 rows more.

Dec 1 st at each end of the next and every foll 12th row until 7 sts rem.

Wk 17 rows straight.

Cast off in patt.

Handles (make 2)

Using 5½mm needles and M, cast on 5 sts.

Wk 51cm in moss st patt as given for back and front when slightly stretched (alter length if required.)

Cast off in patt.

Thread handle through rings, and sew cast on or off edge to enclose the ring.

Pocket lining

Using 5½mm needles and C, cast on 25 sts.

Wk 24 rows in st st, ending with a P row.

Leave sts on a st holder.

Front lining

Using 5½mm needles and C, cast on 49 sts.

Beg with a K row, cont in st st, dec 1 st at each end of the 21st and every foll 16th row until 43 sts rem.

Wk 5 rows straight, ending with a P row.

Cast off.

Back lining

Using 5½mm needles and C, cast on 49 sts.

Beg with a K row, cont in st st, dec 1 st at each end of the 21st and foll 16th row. 45 sts.

Wk 9 rows straight, ending with a P row.

Insert pocket

Next row – K10, sl next 25 sts onto a st holder, K across 25 sts from pocket lining, K10. 45 sts.

Wk 5 rows straight, ending with a P row.

Dec 1 st at each end of of the next row.

Wk 5 rows straight, ending with a P row.

Cast off rem 43 sts.

Lining sides and base

Using 5 ½ mm needles and C, cast on 8 sts.

Wk 4 rows in st st, ending with a P row.

Inc 1 st at each end of the next and every foll 8th row until 20 sts are on the needle.

Wk 13 rows straight.

(Mark each end of last row to indicate start of base.)

Cont in st st until wk (when slightly stretched) fits across cast on edge of back, ending with a P row.

(Mark each end of last row to indicate end of base.)

Wk 14 rows more.

Dec 1 st at each end of the next and every foll 8th row until 8 sts rem.

Wk 3 rows straight, ending with a P row.

Cast off.

Pocket edging

Using 5½mm needles and C, and with RS facing, wk across sts on st holder as follows:-

Next row – K1, *P1, K1, rep from * to end.

Wk 5 rows more in moss st patt.

Cast off in patt.

To complete

Sew back and front to sides and base.

Sew pocket edging and pocket lining into position.

Sew back and front linings to lining sides and base. Turn inside out.

Place lining inside bag. Sew top edge of lining to first row of moss st patt all round bag.

Fold moss st around top of bag in half and sew to top of lining, leaving st st flaps free.

Sew in zip



Cygnet Yarns Limited

12-14 Adelaide Street, Bradford, West Yorkshire, BD5 0EA

CY1112© 2018 Designed and published by Cygnet Yarns Limited of 12-14 Adelaide Street, Bradford, BD5 0EA. This pattern is protected by the law of Copyright of the United Kingdom and may not be reproduced or copied. This pattern maybe used for manufacturing purposes up to a limit of 20 garments. For anything more than this, please contact CYGNET YARNS LTD. All other rights are expressly reserved by CYGNET YARNS LTD.